

Date Revised: 7/14/2015

Supersedes: 03/03/2015

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name(s):	Five Star [®] Epoxy Novolac Grout/Component B Hardener Five Star [®] Novolac Structural Concrete/Component B Hardener
Synonyms:	Epoxy Novolac Hardener/Novolac Epoxy Hardener
Product Use:	For use with Five Star Epoxy Aggregate and Five Star Novolac Epoxy Resin
Restrictions on Use:	To be used with specific Five Star [®] systems.
Manufacturer/Supplier	Five Star Products, Inc. 60 Parrot Drive Shelton, CT 06484
Phone #:	203-336-7900
Emergency Phone #:	CHEM-TEL 1-800-255-3924 (Outside the U.S. 1-813-248-0585)

SECTION 2: HAZARD(S) IDENTIFICATION-GHS INFORMATION

Classification:	Acute Toxicity – Oral, Category 4 Acute Toxicity – Dermal, Category 3 Skin Corrosion – Category 1 Eye Damage – Category 1 Sensitization – Respiratory, Category 1 Sensitization – Skin, Category 1
Label Elements/Hazard Pictograms:	
Signal Word:	Danger
Hazard Statements:	Harmful if swallowed, H302 Toxic in contact with skin, H311 Causes severe skin burns and eye damage, H314 May cause an allergic skin reaction, H317 May cause respiratory irritation, H335
Precautionary Statements/Prevention:	Do not breathe dust, fume, gas, mist, vapors, or spray, P260 Wash thoroughly after handling, P264 Do not eat, drink or smoke when using this product, P270 Contaminated work clothing should not be allowed out of the workplace, P272 Wear protective gloves, protective clothing, eye protection and face protection, P280

Wear respiratory protection, P284



Date Revised: 7/14/2015

Supersedes: 03/03/2015

Response:	 If swallowed: Rinse mouth. Do NOT induce vomiting, P330, P331. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower, P361, P353. If inhaled: Remove person to fresh air and keep comfortable for breathing, P340. If in eyes: Rinse cautiously with water for several minutes, P351. Remove contact lenses, if present and easy to do. Continue rinsing, P338. Immediately call a poison center or doctor, P310. If skin irritation or rash occurs, P333: Get medical advice/attention, P313. If experiencing respiratory symptoms, P342: Call a poison center or doctor, P310. Wash contaminated clothing before reuse, P363.
Storage:	Store locked up.
Disposal:	Dispose of contents/container in accordance with applicable regional, national, and local laws and regulations.
Hazards Not Otherwise Classified:	Not applicable
Ingredients with Unknown Toxicity:	Some of this product mixture may contain ingredients of unknown acute toxicity.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS		
Hazardous Ingredient(s)	Common Name/Synonyms	CAS No.
Aromatic Amine	Trade Secret	Trade Secret
1,2-Ethanediamine, N1-(2- aminoethyl)-N2-[2-[(2- aminoethyl)amino]ethyl]	ТЕРА	112-57-2
Tertiary Amines	Not available	Trade Secret
Aliphatic Amines	Not applicable	Trade Secret

SECTION 4: FIRST AID MEASURES	
Inhalation:	If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or doctor.
	Acute and delayed symptoms and effects: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause

asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Signs/symptoms may include burning pain in the nose and throat, coughing, wheezing, shortness of breath and pulmonary edema.



Date Revised: 7/14/2015

Supersedes: 03/03/2015

Eye Contact:	If in eyes: Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. Acute and delayed symptoms and effects: Causes serious eye damage. Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.
Skin Contact:	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower for at least 15 minutes. Immediately call a poison center or doctor. Wash contaminated clothing before reuse.
	Acute and delayed symptoms and effects: Toxic in contact with skin. May cause an allergic skin reaction. Causes severe skin burns. Signs/symptoms may include localized redness, swelling, itching, intense pain, and blistering, ulceration, and tissue destruction.
Ingestion:	If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Never give anything by mouth to an unconscious person.
	Acute and delayed symptoms and effects: Harmful if swallowed. Causes burns to nose, mouth, throat, and digestive tract. Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea, blood in the feces and/or vomitus may also be seen.
General Advice:	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible). First Aid responders should pay attention to self-protection and use recommended protective clothing (chemical resistant gloves, splash protection).
Note to Physicians:	Symptoms may not appear immediately. Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES	
Flammability and Explosion Information:	Not flammable or combustible by OSHA/WHMIS criteria.
MEANS OF EXTINCTION	
Suitable Extinguishing Media:	Small Fire: Dry chemical, CO2 or water spray.
	Large Fire: Dry chemical, CO2, alcohol-resistant foam or water spray. Move containers from fire area if you can do it without risk. Dike fire- control water for later disposal; do not scatter the material.
Unsuitable Extinguishing Media:	Do not use water jet. Product will float and can be reignited on the surface of the water.
Products of Combustion:	Oxides of carbon, oxides of nitrogen, ammonia.



Supersedes: 03/03/2015

Protection of Firefighters:	TOXIC; inhalation, ingestion or skin contact with material may cause severe injury or death. Contact with molten substance may cause severe burns to skin and eyes. Avoid any skin contact. Effects of contact or inhalation may be delayed. Fire may produce irritating, corrosive and/or toxic gases. Runoff from fire control or dilution water may be corrosive and/or toxic and cause pollution. Wear positive pressure self- contained breathing apparatus (SCBA). Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection. Structural firefighters' protective clothing provides limited protection in fire
	firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedures:	As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet). Stay upwind. Keep out of low areas. Ventilate enclosed areas. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
Personal Precautions:	Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Use personal protection recommended in Section 8.
Environmental Precautions:	Prevent entry into waterways, sewers, basements or confined areas.
Methods for Containment:	Stop leak if you can do it without risk.
Methods for Clean-Up:	Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
Other Information:	See Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

Handling:	Do not swallow. Do not breathe mist, vapors, or spray. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. See Section 8 for information on Personal Protective Equipment.
Storage:	Store locked up. Store away from incompatible Materials. See Section 10 for information on Incompatible Materials. Keep out of the reach of children.



Supersedes: 03/03/2015

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Component	CAS No.	ACGIH(PEL)	OSHA(TLV)
Aromatic Amine	Trade Secret	Not established	Not established
1,2-Ethanediamine, N1-(2- aminoethyl)-N2-[2-[(2- aminoethyl)amino]ethyl]	112-57-2	Not established	Not established
Tertiary Amines	Trade Secret	Not established	Not established
Aliphatic Amines	Trade Secret	Not established	Not established

PEL: Permissible Exposure Limit TLV: Threshold Limit Value

Engineering Controls: Not normally required.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Eye/Face Protection:	Wear chemical safety goggles and full face shield. Ensure that eyewash stations and safety showers are close to the workstation location. Use equipment for eye protection that meets the standards referenced for OSHA regulations in 29 CFR 1910.133 for Personal Protective Equipment.
Hand Protection:	Wear protective gloves. Rubber or polyethylene material is recommended. Consult manufacturer specifications for further information.
Skin and Body Protection:	Wear protective clothing. Clothing with full length sleeves and pants should be worn.
Respiratory Protection:	Wear respiratory protection. If engineering controls and ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator with organic vapor cartridge, or self-contained breathing apparatus must be sued when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.
General Hygiene Considerations:	Handle according to established industrial hygiene and safety practices.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES	
Appearance:	Reddish brown liquid.
Color:	Reddish brown.
Odor:	Strong, ammoniacal
Odor Threshold:	N/A
Physical State:	Liquid



Date Revised: 7/14/2015

Supersedes: 03/03/2015

pH:	alkaline
Melting Point / Freezing Point:	Not available
Initial Boiling Point:	Not available
Boiling Point:	> 100° C (212°F)
Flash Point:	> 93.4° C (200.1°F)
Evaporation Rate:	Not available.
Flammability (solid, gas):	Not available.
Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.
Vapor Pressure:	<1.33 mbar
Vapor Density:	> 1 (Air=1)
Relative Density:	1.02-1.03 (Water=1)
Solubility:	Partially soluble in water
Partition Coefficient: n-Octanol/Water:	Not available.
Auto-ignition Temperature:	Can auto-ignite in air at approximately 572°F (300°C)
Decomposition Temperature:	Not available
Viscosity:	20-50
Percent Volatile, wt.%:	0%
VOC Content, wt.%:	0%
Density:	Not available
Coefficient of Water/Oil Distribution:	Not available

SECTION 10: STABILITY AND REACTIVITY Chemical Stability: Stable under normal conditions.

Hazardous decomposition byproducts:	Oxides of carbon, oxides of nitrogen, ammonia.
Conditions to Avoid:	Can auto-ignite in air at approximately 572°F (300°C)
Incompatible Materials:	Epoxy resins under uncontrolled conditions, acid, oxidizing material, halogenated, organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity

Primary Irritant Effect	
On the Skin:	Irritant to skin and mucous membranes.



Primary Irritant Effect	
On the Eye:	Irritating effect.
Swallowing:	Can cause abdominal irritation, nausea, vomiting, and diarrhea.
Additional Toxicological Information:	This product has no carcinogens listed by IARC, NTP, NIOSH, OSHA, or ACGIH as of this date, greater or equal to 0.1%

SECTION 12: ECOLOGICAL INFORMATION

Toxicity:	All work practices must be aimed at eliminating environmental contamination.
Aquatic Toxicity:	This material is harmful to the environment.
Persistence and Degradability:	The product is partially biodegradable. Significant residue remains.
Bio-accumulative Potential:	Does not accumulate in organisms.
Mobility in Soil:	No further relevant information available
Ecotoxical Effects Remark:	Toxic for fish. Due to mechanical actions of the product damages may occur. The declared action may be partly caused by lack of oxygen.
Additional Ecological Information:	No further relevant information available
General Notes:	No further relevant information available
PBT Assessment:	N/A
vPvB Assessment:	N/A
Other Adverse Effects:	No further relevant information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Recommendation:	The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
	Care should be taken when handling emptied containers t h a t have not been cleaned or rinsed out. Empty containers and liners may retain some product residues. Vapor from some product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
	Processing, use or contamination may change the waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with



Date Revised: 7/14/2015

Supersedes: 03/03/2015

	regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal.
	ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES.
Uncleaned Packaging:	Empty containers may contain residue and may be dangerous. Do not attempt to refill or clean without proper instructions. Empty drums should be drained and stored safely for reconditioning or recycling.
Recommendation:	Disposal must be made according to official regulations.

SECTION 14: TRANSPORT INFORMATION

US DEPARTMENT of TRANSPORTION (DOT) Proper Shipping Name:	UN2735, AMINES, LIQUID, CORROSIVE, NOS (AROMATIC AMINES/ TETRAETHYLENEPENTAMINE) 8, PG III
Class:	8
UN #:	UN2735
Packing Group:	III
Air Transport: ICAO- IATA/DGR (Cargo) Proper Shipping Name:	UN2735, AMINES, LIQUID, CORROSIVE, NOS (AROMATIC AMINES/ TETRAETHYLENEPENTAMINE) 8, PG III
Class:	8
UN#:	UN2735
Packing Group:	III
Sea Transport: (IMDG- Code/GGVSee):	UN2735, AMINES, LIQUID, CORROSIVE, NOS (AROMATIC AMINES/ TETRAETHYLENEPENTAMINE) 8, PG III
Class:	8
UN #:	UN2735
Packing Group:	III
CANADA Transportation of Dangerous Goods (TDG) Proper Shipping Name:	UN2735, AMINES, LIQUID, CORROSIVE, NOS (AROMATIC AMINES/ TETRAETHYLENEPENTAMINE) 8, PG III
Class:	8
UN #:	UN2735
Packing Group:	III

SECTION 15: REGULATORY INFORMATION

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.



Safety Data Sheet

Date Revised: 7/14/2015

Supersedes: 03/03/2015

CANADA (DSL):	The components of this product are in compliance with the chemical notification requirements of NSN Regulations under CEPA, 1999.	
FEDERAL REGULATIONS		
CANADA:	n/a	
WHMIS Classification:	n/a	
UNITED STATES:	This SDS has been prepared to meet the US OSHA Hazard Communication Standard, 29 CFR 1910.1200	
SARA Title III:	No components are listed.	
STATE REGULATIONS		
Massachusetts:	US Massachusetts Commonwealth's Right-to-Know Las (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)	
New Jersey:	US New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)	
Pennsylvania:	US Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)	
California California Prop 65:	This product does not contain chemicals known to the State of California to be Carcinogenic.	
SECTION 16: OTHER INFORMATION		
Disclaimer:	This information is furnished without warranty of any kind, expressed or implied. Five Star Products, Inc. bases the information and recommendations in this document on data believed to be current and	

HMIS (Hazardous Material Information System:	Health	Flammability	Reactivity	Personal Protection
	3	1	1	E

accurate.



Date Revised: 5/21/2015

Supersedes: 11/20/2014

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name(s):	Five Star® DP Epoxy Grout / Component C Aggregate Five Star® DP Epoxy Grout PG / Component C Aggregate Five Star® DP Epoxy Grout High Flow / Component C Aggregate Five Star® Elastomeric Grout / Component C Aggregate Five Star® Epoxy Grout N / Component C Aggregate Five Star® Epoxy Grout Red N / Component C Aggregate Five Star® Epoxy Novolac Grout / Component C Aggregate Five Star® Epoxy Novolac Grout / Component C Aggregate Five Star® Pile Jacket Epoxy Grout HP/Component C Aggregate Five Star® HP Epoxy Grout / Component C Aggregate Five Star® Rapid Surface Repair Easy Mix/Component C Aggregate Five Star® SP Epoxy Grout / Component C Aggregate
Synonyms:	Aggregate, Component C
Product Use:	Aggregate for reactive polymer construction products. Designed for use with appropriate hardener and resin.
Restrictions on Use:	N/A
Manufacturer/Supplier	Five Star Products, Inc. 750 Commerce Drive Fairfield, CT 06825 USA
Phone #:	203-336-7900
Emergency Phone #:	CHEM-TEL 1-800-255-3924 (Outside the U.S. 1-813-248-0585)

SECTION 2: HAZARD(S) IDENTIFICATION-GHS INFORMATION

Classification:	Eye Damage/Irritation – Category 1 Sensitization – Respiratory, Category 1 Carcinogenicity – Category 1A Specific Target Organ Systemic Toxicity (Single Exposure) – Cat 3 Specific Target Organ Toxicity (Repeated Exposure) – Cat 2
Label Elements/Hazard Pictograms:	
Signal Word:	Warning



Date Revised: 5/21/2015

Supersedes: 11/20/2014

Hazard Statements:	Harmful if swallowed H302 May cause respiratory irritation H335 May cause cancer by inhalation H350 May cause damage to organs through prolonged or repeat exposure H373
Precautionary Statements/Prevention:	Do not breathe dust, fume, gas, mist, vapors, or spray, P260. Wash thoroughly after handling, P264. Wear protective gloves, protective clothing, eye protection and face protection, P280. Wear respiratory protection, P284.
Response:	 If swallowed: Rinse mouth. Do NOT induce vomiting, P330, P331. If inhaled: Remove person to fresh air and keep comfortable for breathing, P340. If in eyes: Rinse cautiously with water for several minutes, P351. Remove contact lenses, if present and easy to do. Continue rinsing, P338. Immediately call a poison center or doctor, P310. If skin irritation or rash occurs, P333: Get medical advice/attention, P313. If experiencing respiratory symptoms, P342: Call a poison center or doctor, P310. Wash contaminated clothing before reuse, P363.
Storage:	Store locked up.
Disposal:	Dispose of contents/container in accordance with applicable regional, national, and local laws and regulations.
Hazards Not Otherwise Classified:	Not applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS			
Hazardous Ingredient(s)	Common Name/Synonyms	CAS No.	% wt/wt
Quartz	Silicon Dioxide, Silica Sand, Crystalline Silica	14808-60-7	65-90
Amorphous Silica Mixture	n/a	TS	10-35

SECTION 4: FIRST AID MEASURES

Inhalation:

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms call poison center or doctor.



Date Revised: 5/21/2015

Supersedes: 11/20/2014

Eye Contact:	If in eyes: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin Contact:	Wash skin thoroughly.
Ingestion:	If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Never give anything by mouth to an unconscious person.
General Advice:	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).
Note to Physicians:	Symptoms may not appear immediately. Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES		
Flammability and Explosion Information:	Not flammable or combustible by OSHA/WHMIS criteria.	
Sensitivity to Mechanical Impact:	This material is not sensitive to mechanical impact.	
Sensitivity to Static Discharge:	This material is not sensitive to static discharge.	
MEANS OF EXTINCTION		
Suitable Extinguishing Media:	Small Fire: Dry chemical, CO2, or water spray. Large Fire: Dry chemical, CO2, alcohol-resistant foam or water spray. Move containers from fire area if you can do it without risk. Dike fire- control water for later disposal; do not scatter the material.	
Unsuitable Extinguishing Media:	Not available	
Product of Combustion:	Non-combustible	
Protection of Firefighters:	As in any fire, wear self-contained breathing apparatus pressure- demand, MSHA/NIOSH (approved or equivalent) and full protective gear.	

SECTION 6: ACCIDENTAL RELEASE MEASURES		
Emergency Procedures:	Use personal protective equipment. Ensure adequate ventilation. Keep people from spill. Avoid dust formation.	
Personal Precautions:	Avoid inhalation of dust. Do not get into eyes, on skin, or clothing.	
Environmental Precautions:	The environmental impact of this product has not been fully investigated.	



Date Revised: 5/21/2015

Supersedes: 11/20/2014

Methods for Containment:	Cover powder spill with plastic sheet or tarp to minimize spreading. Collect this material into a disposal container by sucking or sweeping up.
Methods for Cleanup:	Pick up and transfer to properly labeled containers.
Other Information:	See Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE	
Handling:	Wear personal protective equipment. Ensure adequate ventilation. Avoid dust formation. Do not breathe dust. Prevent contact with skin, eyes, and clothing. Wash thoroughly after handling.
Storage:	Keep containers tightly closed in a cool, dry, and well-ventilated place. Store locked up.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Component	CAS No.	ACGIH TLV	OSHA PEL
Quartz	14808-60-7	TWA: 0.025mg/m ³ respirable fraction	30/(%SiO2+2) mg/m ³ TWA, Total Dust;250/%SiO2+5) mppcf TWA, respirable fraction; 10/(%SiO2+2) mg/m ³ TWA, respirable TWA: 0.1 mg/m ³ (vacated)

PEL: Permissible Exposure Limit TLV: Threshold Limit Value

Engineering Controls: Not normally required.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Eye/Face Protection:	Tightly fitting safety goggles
Hand Protection:	Impervious gloves. Impervious clothing.
Skin and Body Protection:	Impervious gloves. Impervious clothing.
Respiratory Protection:	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive- pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations:	Handle according to established industrial hygiene and safety practices.



Date Revised: 5/21/2015

Supersedes: 11/20/2014

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES		
Appearance:	Granular Powder	
Color:	Gray, Tan, Pink	
Odor:	None	
Odor Threshold:	None	
Physical State:	Solid, powder	
pH:	1:1 W/O Water=12	
Melting Point / Freezing Point:	n/a	
Initial Boiling Point:	n/a	
Boiling Point:	n/a	
Flash Point:	n/a	
Evaporation Rate:	n/a	
Flammability (solid, gas):	n/a	
Lower Flammability Limit:	n/a	
Upper Flammability Limit:	n/a	
Vapor Pressure:	n/a	
Vapor Density:	n/a	
Relative Density:	2.5-2.8	
Solubility:	Negligible	
Partition Coefficient: n-Octanol/Water:	n/a	
Auto-ignition Temperature:	n/a	
Decomposition Temperature:	n/a	
Viscosity:	n/a	
Percent Volatile, wt.%:	n/a	
VOC Content, wt.%:	n/a	
Density:	n/a	
Coefficient of Water/Oil Distribution:	n/a	

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability:	Stable under recommended storage conditions.
Possibility of Hazardous Reactions:	None under normal processing.
Conditions to Avoid:	Exposure to water – product may harden on contact with water.



Incompatible Materials: Strong acids.

SECTION 11: TOXICOLOGICAL INFORMATION			
Information on likely rou	tes of exposure		
Product information:			
Inhalation:	Irritating to respiratory system. Irritating to mucous membranes.		
Eye contact:	Risk of serious damage to eyes.		
Skin contact:	Irritating to skin. May cause allergic skin reaction.		
Ingestion:	Harmful if swallowed.		
Component information:			
Chemical Name: Quartz	LD50 Oral: 500 mg/kg (Rat) ACGIH: A2 – Suspected Human Carcinogen		
IARC: Group 1 – Carcinoger	nic to humans OSHA: X-present		

Delayed and immediate effects and also chronic effects from short and long term exposure.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity:

Aquatic Toxicity:	The environmental impact of this product has not been fully investigated.		
Persistence and Degradability:	No information available.		
Bio-accumulative Potential:	Does not accumulate in organisms		
Mobility in Soil:	No further relevant information available		
Ecotoxical Effects Remark:	No information available.		
Additional Ecological Information:	No information available.		
General Notes:	This statement was deduced from products with a similar structure or composition. Due to available data on eliminability/decomposition and bio-accumulation potential prolonged term damage of the environment cannot be excluded. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Poisonous for fish and plankton in water bodies and toxic for aquatic organisms until alkaline pH is neutralized.		
PBT Assessment:	N/A		
vPvB Assessment:	N/A		
Other Adverse Effects:	No further relevant information available		



Supersedes: 11/20/2014

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Recommendation:	This material as supplied is not a hazardous waste according to Federal regulations (40CFR261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered.
Uncleaned Packaging Recommendation:	Disposal must be made according to official regulations. Do not re-use empty containers.

SECTION 14: TRANSPORT INFORMATION

US DEPARTMENT of TRANSPORTATION (DOT) Proper Shipping Name:	Not regulated
Class:	N/A
UN #:	N/A
Packing Group:	N/A
CANADA Transportation of Dangerous Goods (TDG) Proper Shipping Name:	Not regulated
Class:	N/A
UN #:	N/A
Packing Group:	N/A

SECTION 15: REGULATORY INFORMATION

CHEMICAL INVENTORIES	
US (TSCA):	The components of this product are in compliance with the chemical notification requirements of TSCA.
CANADA (DSL):	The components of this product are in compliance with the chemical notification requirements of NSN Regulations under CEPA, 1999.
U.S. FEDERAL REGULATIONS	Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the CFR, Part 372.
UNITED STATES:	This SDS has been prepared to meet the US OSHA Hazard Communication Standard, 29 CFR 1910.1200

Five Star	Safety D	ata S	Sheet			5/21/2015 11/20/2014	
SARA 311/312 Hazard Categories	Acute health Chronic Healt Fire Hazard – Sudden Relea Reactive Haza	th hazard · No ase of Pres	– Yes				
US STATE Right to Know Regulations	Chemical Name	NJ	MA	PA	IL	RI	
	Quartz	X	X	X		X]
California California Prop 65:	This product Chemical Nar		-				nogen

SECTION 16: OTHER INFORMATION	
Disclaimer:	The information contained in this document applies to the specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for one's own particular use.