

## KHE 2444 (606154420) 1" Combination hammer Plastic Carry Case

Order no. 606154420  
EAN 4007430213167



Representative picture



- Combination hammer with 3 functions: hammer drilling, drilling, and chiseling
- Vario (V)-electronics for working at customized speeds to suit various application materials.
- Metabo S-automatic torque limiting clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly.
- Lockable switch for trouble-free working in continuous operation

## Technical values

### Parameters

Max. single blow energy (EPTA)	2.3 J
Maximum impact rate	5400 BPM
Rated input power	800 W
Max. capacity in concrete with hammer drills	1 "
Max. capacity in masonry with core bits	2 5/8 "
Max. capacity in steel	1/2 "
Max. capacity in soft wood	1 3/16 "
No-load speed	0 - 1230 RPM
Revolutions at rated load	880 RPM
Bit retainer	SDS-plus
Collar diameter	1 11/16 "
Weight (without power cable)	5.3 lbs
Cable length	13 ft

### Vibration

Hammer drilling concrete	13.7 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Chiseling	15 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	87 dB(A)
Sound power level (LWA)	98 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Hammer chuck for tools with SDS-plus shank end  
Side Handle  
Drilling depth guide  
Plastic carrying case