

W 11-125 Quick (603623420) Angle grinder Cardboard box

Order no. 603623420

EAN 4061792176294



Representative picture



- Low fatigue as never before: compact angle grinder with smallest handle circumference in its class for perfect ergonomics
- Longer service life, more drive: the Metabo LongLife Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Quick disc change at the push of a button without tools, with the Metabo M-Quick System
- Tool-free adjustable guard; twist-proof
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user protection and swift progress
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor
- Suitable for 120 Volt direct current (DC)

Technical values

Parameters

| | |
|------------------------------|---------------|
| Amps | 11 AMPS |
| Grinding wheel Ø | 4 1/2 / 5 " |
| Rated input power | 1100 W |
| Output power | 720 W |
| No-load speed | 11000 RPM |
| Revolutions at rated load | 7500 RPM |
| Torque | 3.2 in-lbs |
| Spindle thread | 5/8" - 11 UNC |
| Weight (without power cable) | 5.1 lbs |
| Cable length | 8 ft |

Vibration

| | |
|------------------------------|----------------------|
| Surface grinding | 5.8 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.6 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 94 dB(A) |
| Sound power level (LWA) | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Guard
 Inner support flange
 M-Quick flange nut
 Side handle Metabo VibraTech (MVT)