

W 26-230 MVT non-locking (US606474760) 9" Angle grinder Cardboard box

Order no. US606474760
EAN



Representative picture



- Metabo safety switch prevents unintentional start-up
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Side handle can be mounted at three positions
- Swivelling main handle: high safety and better handling when cutting
- Auto-stop carbon brushes to protect the motor

Technical values

Parameters

| | |
|------------------------------|---------------|
| Amps | 15 AMPS |
| Grinding wheel Ø | 9 " |
| No-load speed | 6600 RPM |
| Revolutions at rated load | 4800 RPM |
| Torque | 160 in-lbs |
| Spindle thread | 5/8" - 11 UNC |
| Weight (without power cable) | 13.9 lbs |
| Cable length | 13 ft |

Vibration

| | |
|------------------------------|----------------------|
| Surface grinding | 6.4 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 94 dB(A) |
| Sound power level (LWA) | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Cardboard box