

WE 15-125 Quick (600448420) Angle grinder **Cardboard box**

Order no. 600448420 EAN 4007430306616



Representative picture













- Highest service life for extreme applications: robust, powerful angle grinder with greatest power density in its class for quick work progress
- Longer service life, more drive: the Metabo LongLife Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load
- Quick disc change at the push of a button without tools, with the Metabo M-Quick System
- Tool-free adjustable guard; twist-proof
- Low vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user protection and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical values		
Parameters		
Amps	13.5 AMPS	
Grinding wheel Ø	5 "	
Rated input power	1550 W	
Output power	900 W	
No-load speed	11000 RPM	
Revolutions at rated load	11000 RPM	
Torque	31 in-lbs	
Spindle thread	5/8" - 11 UNC	
Weight (without power cable)	5.5 lbs	
Cable length	8 ft	
Vibration		
Surface grinding	6 m/s²	
Uncertainty of measurement K	1.5 m/s²	
Grinding with sandpaper	3.6 m/s ²	
Uncertainty of measurement K	1.5 m/s²	
Noise emission		
Sound pressure level	93 dB(A)	
Sound power level (LwA)	104 dB(A)	
Uncertainty of measurement K	3 dB(A)	

Scope of delivery

Guard

Inner support flange

M-Quick flange nut

Side handle Metabo VibraTech (MVT)

www.metabo.com 2 / 2