

**WPB 13-125 Quick DS (600437420) Angle grinder**  
**Cardboard box**

Order no. 600437420  
EAN 4061792181915



Representative picture



- Long service life for demanding applications: powerful and robust angle grinder with highest power density in its class for quick work progress
- Steel ring for carabiner to secure the angle grinder from falling when working at great heights
- Longer service life, more drive: the Metabo LongLife Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Quick disc change at the push of a button without tools, with the Metabo M-Quick System
- Tool-free adjustable guard; twist-proof
- Low vibration side handle Metabo VibraTech (MVT)
- Paddle switch with dead-man function: safe to operate due to an ergonomically integrated non-slip switch
- Fastest brake system for the highest user protection: patented, mechanical disc brake stops the disc after switching off within 2 seconds, even in the event of a power cut
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user protection and swift progress
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical values

### Parameters

Amps	12 AMPS
Grinding wheel Ø	5 "
Output power	850 W
No-load speed	11000 RPM
Revolutions at rated load	8000 RPM
Torque	30.1 in-lbs
Spindle thread	5/8" - 11 UNC
Weight (without power cable)	5.7 lbs
Cable length	8 ft

### Vibration

Surface grinding	6 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	93 dB(A)
Sound power level (LWA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard  
Inner support flange  
M-Quick flange nut  
Side handle Metabo VibraTech (MVT)