

WPB 18 LTX BL 150 (613076640) 6" Cordless Angle Grinder 18V 2x8Ah LiHD; Charger ASC 30-36 V; Plastic Carry Case

Order no. 613076640 EAN 4007430290762



Representative picture



- Versatile cordless angle grinder including two guards for grinding (4-1/2") and cutting (6") applications
- Unique encapsulated Metabo brushless motor with optimum protection from dust provides quick work progress and the highest efficiency for any application
- Slim design for prolonged comfort when working overhead or in areas with limited space
- Paddle switch with dead-man function: safe to operate due to an ergonomically integrated non-slip switch
- Quick braking system for the highest level of User Safety stops the disc in seconds after switching off
- Tool-free adjustable guard; twist-proof
- Battery pack can be swiveled for better working in hard to reach places.
- Electronic safety shutdown of the motor reduces kickback if the disc stops unexpectedly- for high user protection
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power supply interruption
- Detachable dust filter protects motor from coarse particles
- LiHD Battery Pack for ultimate power, extremely long run time and service life
- Ultra-M Technology: highest power, gentle charging, and 3 year warranty on the battery pack
- Battery packs with capacity display for checking the charge status



Technical values

Parameters

Type of battery pack	LiHD
Battery capacity	8 Ah
Battery voltage	18 V
Grinding wheel Ø	6 "
No-load speed	9000 RPM
Spindle thread	5/8" - 11 UNC
Weight (including battery pack)	5.7 lbs
Vibration	
Surface grinding	5 m/s²
Surface grinding Uncertainty of measurement K	5 m/s ² 1.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Uncertainty of measurement K Grinding with sandpaper	1.5 m/s ² 2.5 m/s ²
Uncertainty of measurement K Grinding with sandpaper Uncertainty of measurement K	1.5 m/s ² 2.5 m/s ²
Uncertainty of measurement K Grinding with sandpaper Uncertainty of measurement K Noise emission	1.5 m/s ² 2.5 m/s ² 1.5 m/s ²

Scope of delivery

Clip-on cutting wheel guard 6" Plastic carrying case 2 guards (4 1/2" and 6") Inner support flange Nut with two holes Side Handle Dust Protection Filter Spanner wrench 2 LiHD Battery Packs (18 V/8.0 Ah) Charger ASC 30-36 V "AIR COOLED"