



PERMA-PATCH PRODUCT DATA SHEET

- Description:** A high tech cold patch repair material which consists of a unique blend of special chemical additives, pressure sensitive plastics, asphalt and special aggregates.
- Characteristics:** Perma-Patch can be applied in any weather conditions, in temperatures from -15 to over 100 degrees F without mixing, tack coating, or any other type of sealer applied.
- Use:** A quick and permanent repair of potholes and utility/cable cuts.
- Bonding:** Perma-Patch will bond to stone, concrete, asphalt, wood and metal. it will not adhere to rubber tires.
- Application:** Perma-Patch is poured directly from bag into pothole; there is no need to remove standing water or small aggregate. Compaction can be accomplished with vehicular traffic, hand tamping or for larger areas, a vibrating plate compactor.
- Curing:** Surface hardening occurs through dynamic pressure. Layers beneath the surface remain semi-soft to expand and contract with the changes in pressure and temperature.
- Packaging:** Perma-Patch comes in 60-pound lined Kraft bags.
- Coverage:** A bag of Perma-Patch fills 0.47 cubic ft.

www.permapatch.com

Perma-Patch, Inc.

A subsidiary of
The National Paving & Contracting Co.
6123 Oakleaf Avenue
Baltimore, MD 21215
Phone 410-764-7117
Fax 410-764-7137