

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

### | Identification

- · Product identifier
- · Trade name: Pile Anchor Grout Component A
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Product description Epoxy Grout
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E-Chem, LLC

2944 William Street SE Albuquerque, NM 87102 Phone: 505. 217.2121

Fax: 505.217.3721 Email: mail@e-chem.net Web: www.e-chem.net

Emergency telephone number: Chemtrec at 1-800-424-9300 24 Hours

Outside the U.S., call Chemtrec collect at 703-527-3887

# Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

H350 May cause cancer.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure:

Inhalative.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

Eye Irrit. 2B H320 Causes eye irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Quartz (SiO2) titanium dioxide

(Contd. on page 2)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

#### Trade name: Pile Anchor Grout - Component A

(Contd. of page 1)

#### · Hazard statements

Causes skin and eye irritation.

May cause cancer.

May cause respiratory irritation.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalative.

#### · Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

# Unknown acute toxicity:

90 percent of the mixture consists of ingredient(s) of unknown toxicity.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 1

Reactivity = 0

### · HMIS-ratings (scale 0 - 4)



\*3 Health = \*3

1 Fire = 1

Other hazards None known

# Composition/information on ingredients

1317-61-9 Iron Oxide

2-12%

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 2)

Dangerous Components:		
CAS: 25085-99-8	Bisphenol A Based Epoxy Resin  Skin Irrit. 2, H315	25-50%
CAS: 14808-60-7 RTECS: VV 7330000	Quartz (SiO2)	25-50%
CAS: 13463-67-7	titanium dioxide  Carc. 2, H351;  Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	2-12%

### 4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness, place patient securely on side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

#### 6 Accidental release measures

#### · Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 3)

#### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

#### · Handling:

# Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin, eyes and clothing

Avoid breathing fume/gas/mist/vapors/spray.

Do not take internally.

Use personal protection equipment as outlined in section 8.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

#### · Components with occupational exposure limits:

### 14808-60-7 Quartz (SiO2)

PEL see Quartz listing

REL Long-term value: 0.05\* mg/m³

\*respirable dust; See Pocket Guide App. A

TLV | Long-term value: 0.025\* mg/m³

\*as respirable fraction

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

Protection of hands:





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

• Eye protection: Tightly sealed goggles

# 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Viscous
Color: Grey
Odor: Mild

Odor threshold: Not determined.pH-value: Not determined.

· Change in condition

Melting point/Melting range:<br/>Boiling point/Boiling range:Not determined.Flash point:252 °C (486 °F)Flammability (solid, gaseous):Not applicable.

• Ignition temperature: > 300 °C (> 572 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower: Not determined. Not determined.

Vapor pressure: Not determined.

· Density:

Relative densityNot determined.Vapour densityNot determined.Evaporation rateNot determined.

· Solubility in / Miscibility with

Water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 0.0 %
Solids content: 50.0 %

• Other information No further relevant information available.

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 5)

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials:

Strong acids, strong bases

Strong oxidizing agents.

· Hazardous decomposition products:

Nitrogen oxides

Oxides of carbon (COx)

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye:

Irritating effect.

Causes serious eye irritation.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

1			
2B			
· NTP (National Toxicology Program)			
K			
None of the ingredients are listed.			

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes: Not known to be hazardous to water.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 6)

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Do not allow product to reach sewage system.

It is the generators responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state and federal environmental regulations.

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

### 14 Transport information

· UN-Number

· DOT, ADR, ADN, IMDG, IATA Non-Regulated Material

· UN proper shipping name

· DOT, ADR, ADN, IMDG, IATA Non-Regulated Material

· Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Non-Regulated Material

· Packing group

· **DOT, ADR, IMDG, IATA** Non-Regulated Material

· Environmental hazards:

· *Marine pollutant:* No

· Special precautions for user Not applicable.

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation":

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

<ul> <li>Section 355 (extremely hazardous substances):</li> </ul>	Section	355 (extreme	lv hazardous	substances).
---	---------	--------------	--------------	--------------

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

Proposition 65

· Chemicals known to cause cancer:

14808-60-7 Quartz (SiO2)

13463-67-7 titanium dioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 01/21/2015 Printing date 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 7)

· Chemicals known to cause developmental toxicity:	
None of the ingredients are listed.	

· Carcinoger	· Carcinogenic categories			
· EPA (Environmental Protection Agency)				
None of the ingredients are listed.				
· TLV (Threshold Limit Value established by ACGIH)				
14808-60-7	Quartz (SiO2)	A2		
13463-67-7	titanium dioxide	A4		
· NIOSH-Ca (National Institute for Occupational Safety and Health)				
14808-60-7	Quartz (SiO2)			
13463-67-7	titanium dioxide			

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

#### · Hazard pictograms





GHS07 GHS08

#### Signal word Danger

#### · Hazard-determining components of labeling:

Quartz (SiO2)

titanium dioxide

#### · Hazard statements

Causes skin and eye irritation.

May cause cancer.

May cause respiratory irritation.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalative.

#### Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eve irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 8)

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

	· National regulations	:	
	The product is subject to be labeled according with the prevailing version of the regulations on haza substances.		
· State Right to Know			
ľ	CAS: 25085-99-8	Bisphenol A Based Epoxy Resin	25-50%
		♦ Skin Irrit. 2, H315	
	CAS: 14808-60-7	Quartz (SiO2)	25-50%
	RTECS: VV 7330000	♦ Carc. 1A, H350; STOT RE 1, H372; ♦ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	
	CAS: 13463-67-7	titanium dioxide	2-12%
		♦ Carc. 2, H351; ♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
	CAS: 1317-61-9	Iron Oxide	2-12%
ľ	All ingredients are listed.		

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

#### · Date of preparation / last revision 01/21/2015 / 4

# Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

Carc. 1A: Carcinogenicity, Hazard Category 1A

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

#### \* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

### 1 Identification

- · Product identifier
- · Trade name: Pile Anchor Grout B Component
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Product description Epoxy Grout
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E-Chem, LLC

2944 William Street SE Albuquerque, NM 87102 Phone: 505. 217.2121 Fax: 505.217.3721

Email: mail@e-chem.net Web: www.e-chem.net

• Emergency telephone number: Chemtrec at 1-800-424-9300 24 Hours

Outside the U.S., call Chemtrec collect at 703-527-3887

# 2 Hazard(s) identification

#### · Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



#### **GHS05** Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



#### GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS05 GHS07 GHS08



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

#### Trade name: Pile Anchor Grout - B Component

(Contd. of page 1)

### · Signal word Danger

### · Hazard-determining components of labeling:

Tall Oil Fatty Acids, Reaction Product With Tiethylenetetramine triethylenetetramine

#### · Hazard statements

Harmful if swallowed or in contact with skin.

Causes severe skin burns and eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

#### Precautionary statements

Do not breathe dusts or mists.

Wear respiratory protection.

Wear protective gloves.

Wear protective gloves / protective clothing.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

If swallowed: Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If experiencing respiratory symptoms: Call a poison center/doctor.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If swallowed: Rinse mouth, Do NOT induce vomiting.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Unknown acute toxicity:

50 percent of the mixture consists of ingredient(s) of unknown toxicity.

#### Classification system:

# · NFPA ratings (scale 0 - 4)



Health = 3Fire = 1

Reactivity = 0

### · HMIS-ratings (scale 0 - 4)



Health = \*4

1 Fire = 1

Other hazards None known

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - B Component

(Contd. of page 2)

# 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous Components:		
112-24-3 triethylenetetramine		25-50%
	Skin Corr. 1B, H314;  Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
	Tall Oil Fatty Acids, Reaction Product With Tiethylenetetramine	25-50%
	♦ Resp. Sens. 1B, H334;   Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1B, H317; Eye Irrit. 2B, H320	

### 4 First-aid measures

- Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness, place patient securely on side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
  No further relevant information available.

### 5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralizing agent.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

#### Trade name: Pile Anchor Grout - B Component

(Contd. of page 3)

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin, eyes and clothing

Avoid breathing fume/gas/mist/vapors/spray.

Do not take internally.

Use personal protection equipment as outlined in section 8.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · **Specific end use(s)** No further relevant information available.

# 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with occupational exposure limits:

#### 112-24-3 triethylenetetramine

WEEL Long-term value: 6 mg/m³, 1 ppm Skin

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - B Component

(Contd. of page 4)

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection: Tightly sealed goggles

# 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:
Color:
Clear
Odor:
Amine-like
Odor threshold:
Not determined.

PH-value:
Not determined.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:

Flash point:

Flammability (solid, gaseous):

Ignition temperature:

Decomposition temperature:

Not determined.

135 °C (532 °F)

Not applicable.

335 °C (635 °F)

Not determined.

· **Auto igniting:** Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.Upper: Not determined.Vapor pressure: Not determined.

• **Density @ 20 °C (68 °F):** 0.961 g/cm³ (8.02 lbs/gal)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

Solvent content:

Organic solvents: 0.0 %

• Other information No further relevant information available.

#### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - B Component

(Contd. of page 5)

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials:

Strong oxidizing agents.

Strong acids, strong bases

· Hazardous decomposition products: Carbon dioxide, carbon monoxide and nitrogen oxides.

# 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:

2.00.00		· <del>·</del>	
· LD/LC50 values that are relevant for classification:			
112-24-3 triethylenetetramine			
Oral	LD50	2500 mg/kg (rat)	
Dermal	LD50	805 mg/kg (rabbit)	

#### · Primary irritant effect:

on the skin:

Strong caustic effect on skin and mucous membranes.

May cause an allergic skin reaction.

on the eye:

Strong irritant with the danger of severe eye injury.

Corrosive effect.

Causes serious eye irritation.

· Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

#### NTP (National Toxicology Program)

None of the ingredients are listed.

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - B Component

(Contd. of page 6)

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Do not allow product to reach sewage system.

It is the generators responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state and federal environmental regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

# 14 Transp<u>ort information</u>

· UN-Number

DOT UN3267
 ADR, IMDG, IATA UN2259

· UN proper shipping name

Corrosive liquid, basic, organic, n.o.s. (Triethylenetetramine)

ADR

Corrosive liquid, basic, organic, n.o.s. (Triethylenetetramine)

UN2259 Triethylenetetramine mixture

• IMDG, IATA TRIETHYLENETETRAMINE mixture

· Transport hazard class(es)

· DOT



· Class 8 Corrosive substances

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - B Component

(Contd. of page 7)

· Label 8

· ADR



· Class 8 (C7) Corrosive substances

· Label

· IMDG, IATA



· Class 8 Corrosive substances

· Label 8

· Packing group

· DOT, ADR, IMDG, IATA

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Corrosive substances

Danger code (Kemler):
 EMS Number:
 Segregation groups
 Alkalis

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

• **Quantity limitations** On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L

· ADR

• Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· IMDG

· Limited quantities (LQ) 1L

Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN2259, Triethylenetetramine mixture, 8, II

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- Section 355 (extremely hazardous substances):

None of the ingredients are listed.

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - B Component

(Contd. of page 8)

None of the ingredients are listed.

#### · TSCA (Toxic Substances Control Act):

All ingredients are listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

#### · Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

#### · Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

#### · Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

#### · Carcinogenic categories

#### · EPA (Environmental Protection Agency)

None of the ingredients are listed.

#### TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms







GHS05 GHS07 GHS08

#### · Signal word Danger

#### Hazard-determining components of labeling:

Tall Oil Fatty Acids, Reaction Product With Tiethylenetetramine triethylenetetramine

#### · Hazard statements

Harmful if swallowed or in contact with skin.

Causes severe skin burns and eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

### · Precautionary statements

Do not breathe dusts or mists.

Wear respiratory protection.

Wear protective gloves.

Wear protective gloves / protective clothing.

Wear eye protection / face protection.

Avoid release to the environment.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

#### Trade name: Pile Anchor Grout - B Component

(Contd. of page 9)

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

If swallowed: Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If experiencing respiratory symptoms: Call a poison center/doctor.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If swallowed: Rinse mouth. Do NOT induce vomiting.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· State Right to Know			
112-24-3 triethy	lenetetramine	25-50%	
♦ Ski 3, H4	n Corr. 1B, H314; 🗘 Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 12		
	il Fatty Acids, Reaction Product With Tiethylenetetramine sp. Sens. 1B, H334;	25-50%	
All ingredients are listed.			

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

#### · Date of preparation / last revision 01/21/2015 / 3

#### · Abbreviations and acronvms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - B Component

(Contd. of page 10)

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1 Resp. Sens. 1B: Sensitisation - Respirat., Hazard Category 1B Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category  ${\bf 3}$ 

\* \* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106