# TECHNICAL DATA SHEET - MD-1 Form No 61595

# **TRI-COOL**®

# MICRO-DROP® MD-1 VEGETABLE LUBRICANT

An advanced vegetable lubricant for most machining applications.

# **TECHNICAL INFORMATION:**

- •Water Solubility . . . . . . . . . . . . . Insoluble
- Specific Gravity . . . . . . . . . . 0.87

Chemical Makeup:	
sulfurs	. None
chlorines	. None
phenols	
nitrites	. None

# **APPLICATIONS:**

- A high efficiency, vegetable base lubricant for use in sawing, milling, drilling, and tapping operations.
- May be used on ferrous and nonferrous materials.
- For proper application, the use of a MICRO-DROP<sup>®</sup> dispenser is highly recommended.

#### HMIS RATING:

- Health . . . . . . . . . . . . . . . . . 1
- Flammability . . . . . . 0
- Reactivity . . . . . . . . . 0
- Personal Protection . . . 0

TRI-COOL<sup>®</sup> MD-1 lubricant is designed to be used full strength - **DO NOT DILUTE WITH ANY OTHER LIQUID.** 

#### **PERFORMANCE:**

- Effective when used in microscopic amounts as little as .002 ounces per minute.
- Has a heat stable, non-chlorine extreme pressure additive for improved tool life and surface finish.
- Low misting formula to prevent fog in the shop environment.

#### SHOP ENVIRONMENT:

- Cleaner environment no oily fumes, overspray or residues.
- Use of microscopic amounts eliminates spills, overflow, cleanup, and disposal problems.
- Pleasant odor.
- Will not become rancid.

#### **OPERATOR SAFETY:**

- Zero toxicity contains no chlorinated derivatives.
- •Won't support bacteria that causes dermatitis.

# LEGAL COMPLIANCE:

- Does not contain carcinogenic chemicals as listed by OSHA, IARC Monographs, or the National Toxicology Program.
- Meets OSHA and EPA disposal and clean up requirements.

# PACKAGING:

Gallons, Five Gallon Pail, and 55	Gallon Drum
4 - 1 gallon bottles per case	#30648
5 gallon pail	#30647
55 gallon drum	#30646

ALL INFORMATION CONTAINED HEREIN is believed to be reliable and to represent the best available data on this product. Because we cannot control the many different conditions under which this information or this product may be used, no guarantee or warranty, either expressed or implied, is made regarding the correctness or sufficiency of any information, or the suitability of this product in any given situation.



**TRICO MFG. CORP.** 1235 Hickory Street Pewaukee, WI 53072 PRODUCT INFORMATION: Call toll-free 1-800-558-7008 U.S.A. or (262) 691-9336 Fax: (262) 691-2576 Web: www.tricomfg.com