

SAFETY DATA SHEET **UNISORB® PREMIUM NON-SHRINK GROUT** 

# INSTALLATION TECHNOLOGIES

Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards

Section 1: IDENTIFICATION			
1.1 PRODUCT IDENTIFIER			
Product Name & Code:	Unisorb® V-1 Premium Non-Shrink Grout 48lb Bag		
1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE			
Use:	Various.		
1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET			
Name/Address:	Unisorb Installation Technologies 4117 Felters Road, Michigan Center, MI 49254 PO Box 1000 Jackson, MI 49204		
Telephone Number:	517-764-6060 Tech Service 8:00 to 5:00 Eastern, MonFri.		
1.4 EMERGENCY TELEPHONE NUMBER			
Emergency Telephone Number:	CHEM•TEL 800-255-3924 INTERNATIONAL 813-248-0585		
Date of Preparation:	September 12, 2012 Version #: 1.0		
Section 2: HAZARD(S) IDENTIFICATION			

# 2.1 CLASSIFICATION OF THE CHEMICAL

### Hazard class

Acute toxicity 4 (Oral) Skin irritation 2 Serious eye damage 1 Skin sensitization 1 Carcinogenicity 1A Specific target organ toxicity - Single exposure 3

# **2.2 LABEL ELEMENTS**

# Hazard Pictogram:



Signal Word:

Danger

**Hazard Statement:** Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May cause respiratory irritation. Wash hands thoroughly after handling. Do not eat, drink or smoke **Prevention:** 

when using this product. Avoid breathing dust. Contaminated work clothing must not be allowed out of the workplace. Obtain special





STALLATION TECHNOLOGIES

Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards

	instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well- ventilated area.
Response:	If swallowed: Immediately call a poison center/doctor. Rinse mouth. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention.
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store locked up. $\square$
Disposal:	Dispose of contents and container in accordance with all local, regional, national and international regulations.

# 2.3 ADDITIONAL INFORMATION

# Hazards not otherwise classified:

Not applicable.

49 % of the mixture consists of ingredient(s) of unknown acute toxicity.

This product is a hazardous chemical as defined by NOM-018-STPS-2000.

# Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

# 3.1 MIXTURES

Ingredient	UN #	H / F/ R / *	CAS No	Wt. %
Silica, crystalline, quartz	Not available.	Not available.	14808-60-7	30 - 60
Portland cement	Not available.	1/0/0	65997-15-1	30 - 60

The exact percentage (concentration) of chemicals has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

\* Per NOM-018-STPS-2000

Section 4: FIRST- AID MEASURES

# 4.1 DESCRIPTION OF THE FIRST AID MEASURE

Eye:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
Skin:	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
Inhalation:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.





#### Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards

Ingestion:	If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.	
4.2 MOST IMPORTANT SYMPT	OMS AND EFFECTS, BOTH ACUTE AND DELAYED	
Eye:	Risk of serious damage to eyes. May cause serious chemical burns. Severe irritation, redness and pain.	
Skin:	Irritating to skin. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. May cause sensitization by skin contact.	
Inhalation:	May cause respiratory tract irritation.	
Ingestion:	Harmful if swallowed. May cause stomach distress, nausea or vomiting.	
4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED		
Note to Physicians:	Symptoms may not appear immediately.	
Specific Treatments:	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).	

# Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY	
Flammability:	Not flammable by WHMIS/OSHA criteria.
5.2 EXTINGUISHING MEDIA	
Suitable Extinguishing Media:	Treat for surrounding material.

# Unsuitable Extinguishing Media: None known.

# 5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

**Products of Combustion:** May include, and are not limited to: oxides of carbon.

### **Explosion Data:**

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

# 5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA)

## Section 6: ACCIDENTAL RELEASE MEASURES

# 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Avoid any contact with the skin and eyes.





INSTALLATION TECHNOLOGIES

Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards

# 6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

Methods for Containment:	Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods for Cleaning-Up:	Vacuum or sweep material and place in a disposal container.

# Section 7: HANDLING AND STORAGE

# 7.1 PRECAUTIONS FOR SAFE HANDLING

Handling:	Avoid contact with skin and eyes. Do not swallow. Good housekeeping is important to prevent accumulation of dust. Avoid generating and breathing dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking. (See section 8)
General Hygiene Advice:	Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.
7.2 CONDITIONS FOR SAFE ST	FORAGE, INCLUDING ANY INCOMPATIBILITIES
Storage:	Keep out of the reach of children. Store in dust-tight, dry, labeled containers. Keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers. Use corrosion-resistant structural materials and lighting and ventilation systems in the storage area. (See section 10)

# Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1 CONTROL PARAMETERS

# **Exposure Guidelines**

Occupational Exposure Limits			
Ingredient OSHA-PEL ACGIH-TLV		ACGIH-TLV	
Silica, crystalline, quartz	((10 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (resp)) ((30 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (total)) ((250)/(%SiO <sub>2</sub> +5) mppcf TWA (resp))	0.025 mg/m³	
Portland cement	15 mg/m <sup>3</sup> (total); 5 mg/m <sup>3</sup> (resp)	1 mg/m <sup>3</sup> (no asbestos and <1% crystalline silica, respirable fraction)	

# 8.2 EXPOSURE CONTROLS

# **Engineering Controls:**

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.



FETY DATA SHEET

UNISORB® PREMIUM NON-SHRINK GROUT

# **INSTALLATION TECHNOLOGIES**

Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards

# **8.3 INDIVIDUAL PROTECTIVE MEASSURES**

# **Personal Protective Equipment:**

Eye/Face Protection:	Wear approved eye (properly fitted dust- or splash-proof chemical safety goggles) / face (face shield) protection.		
Skin Protection:			
Hand Protect	tion:	Wear suitable gloves.	
Body Protec	tion:	Wear suitable protective clothing, including appropriate boots, boot covers, overshoes, etc., as may be appropriate.	
Respiratory Protection:	poorl exce direc requi	IIOSH approved dust mask or filtering facepiece is recommended in orly ventilated areas or when permissible exposure limits may be eeded. Respirators should be selected by and used under the ection of a trained health and safety professional following uirements found in OSHA's respirator standard (29 CFR 1910.134) I ANSI's standard for respiratory protection (Z88.2).	
General Health and Safety Measures:		o not eat, smoke or drink where material is handled, processed or tored. Wash hands carefully before eating or smoking.	

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Powder.	
Color:	Various.	
Odor:	Characteristic.	
Odor Threshold:	Not available.	
Physical State:	Solid.	
pH:	12 - 13	
Melting Point/Freezing Point:	Not available.	
Initial Boiling Point and Boiling Range:	Not available.	
Flash Point:	Not available.	
Evaporation Rate:	Not available.	
Flammability:	Not Flammable.	
Lower Flammability/Explosive Limit:	Not available.	
Upper Flammability/Explosive Limit:	Not available.	
Vapor Pressure:	Not available.	
Vapor Density:	Not available.	
Relative Density/Specific Gravity:	Not available.	
Solubility:	Not available.	
Partition coefficient: n-octanol/water:	Not available.	
Trade Name: Unisorb® Premium Non-Shrink Grout		Print date: 2012-09-12





# INSTALLATION TECHNOLOGIES

# Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards

Auto-ignition Temperature:	Not available.
Decomposition Temperature:	Not available.
Viscosity:	Not available.
Percent Volatile, wt. %:	Not available.
VOC content, wt. %:	Not available.

# Section 10: STABILITY AND REACTIVITY

### **10.1 REACTIVITY**

No dangerous reaction known under conditions of normal use.

# **10.2 CHEMICAL STABILITY**

Stable under normal storage conditions. Keep dry in storage.

### 10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

# **10.4 CONDITIONS TO AVOID**

Heat. Incompatible materials. Moisture.

# **10.5 INCOMPATIBLE MATERIALS**

None known.

# **10.6 HAZARDOUS DECOMPOSITION PRODUCTS**

May include, and are not limited to: oxides of carbon.

# Section 11: TOXICOLOGICAL INFORMATION

# **11.1 INFORMATION ON TOXICOLOGICAL EFFECTS**

Likely Routes of Exposure:	Skin contact, skin absorption, eye contact, inhalation,
	and ingestion.

# Symptoms related to physical/chemical/toxicological characteristics:

- **Eye:** Risk of serious damage to eyes. May cause serious chemical burns. Severe irritation, redness and pain.
- **Skin:** Irritating to skin. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. May cause sensitization by skin contact.
- Ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting.
- Inhalation: May cause respiratory tract irritation.





# INSTALLATION TECHNOLOGIES

# Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards

# Acute Toxicity:

Addie Texiony.					
Ingredient	IDLH		L	.C50	LD50
Silica, crystalline, quartz Portland cement	Ca [25 mg/m <sup>3</sup> (cristobalite, tridymite); 50 mg/m <sup>3</sup> (quartz, tripoli)] 5000 mg/m <sup>3</sup>			vailable. vailable.	Oral Rat 500 mg/kg Not available.
	Calculat	ted overall Chemical Acut	te Toxici	ity Values	
LC50 (inhalation) LD50 (oral)		LD50 (dermal)			
Not available. 505.1 mg/kg, rat		Not available.			
Ingredient		Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*			
Silica, crystalline, quartz		G-A2, I-1, N-1, CP65			
Portland cement		G-A4			

# 11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation:	Causes skin irritation. May cause burns in the presence of moisture.
Serious Eye Damage/Irritation:	Corrosive to eyes. Causes burns.
Respiratory Sensitization:	Although this product has not been tested, it is not expected to have sensitizing potential, based on the absence of effects with the constituents.
Skin Sensitization:	May cause sensitization by skin contact.
STOT-Single Exposure:	May cause respiratory tract irritation.
	Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.

Carcinogenicity: May cause cancer.

Germ Cell Mutagenicity: This product is not classified as a mutagen.

**Reproductive Toxicity:** 

Developmental: Based on available data, the classification criteria are not met.

Teratogenicity: Not hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Not hazardous by WHMIS/OSHA criteria.

Fertility: Based on available data, the classification criteria are not met.





# INSTALLATION TECHNOLOGIES

# Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards

STOT-Repeated Exposure:	Based on consideration of the components, this product is not expected to cause any specific target organ effects.
Aspiration Hazard:	Not expected to occur.
Toxicologically Synergistic Materials:	Not available.
Other Information:	Not available.

# Section 12: ECOLOGICAL INFORMATION

# **12.1 ECOTOXICITY**

Acute/Chronic Toxicity: No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.

# **12.2 PERSISTENCE AND DEGRADABILITY**

Not available.

# **12.3 BIOACCUMULATIVE POTENTIAL**

**Bioaccumulation:** 

Not available.

# **12.4 MOBILITY IN SOIL**

Not available.

# **12.5 OTHER ADVERSE EFFECTS**

Not available.

Section 13: DISPOSAL CONSIDERATIONS

# **13.1 WASTE TREATMENT METHODS**

**Disposal Method:** 

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Other disposal recommendations:

Not available.

# Section 14: TRANSPORT INFORMATION

14.1 UN NUMBER		
DOT	TDG	NOM-004-SCT2-1994
Not regulated.	Not regulated.	Not regulated.
14.2 UN PROPER SHIPPING NAME		
DOT	TDG	NOM-004-SCT2-1994
Not applicable.	Not applicable.	Not applicable.

Trade Name: Unisorb® Premium Non-Shrink Grout

Print date: 2012-09-12





Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards

14.3 TRANSPORT HAZARD CLAS	S (ES)	
DOT	TDG	NOM-004-SCT2-1994
Not applicable.	Not applicable.	Not applicable.
14.4 PACKING GROUP		
DOT	TDG	NOM-004-SCT2-1994
<b>DOT</b> Not applicable.	<b>TDG</b> Not applicable.	NOM-004-SCT2-1994 Not applicable.
	Not applicable.	

# 14.6 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available.

# 14.7 SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

# Section 15: REGULATORY INFORMATION

# 15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICLA

**Canadian:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**US:** MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SARA Title III				
Ingredient         Section 302 (EHS)         Section 304         CERCLA           TPQ (lbs.)         EHS RQ (lbs.)         RQ (lbs.)         Section 313				
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
Portland cement	Not listed.	Not listed.	Not listed.	Not listed.

Mexico: MSDS prepared pursuant to NOM-018-STPS-2000.

# State Regulations

# California Proposition 65:

This product contains Crystalline Silica, Quartz and may also contain trace amounts of other chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.





# Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards

# **Global Inventories**

Ingredient	Canada DSL/NDSL	USA TSCA	
Silica, crystalline, quartz	DSL	Yes.	
Portland cement	DSL	Yes.	
NFPA - Nat	ional Fire Protection Association:		
Health:		3	
Fire:		1	
Reactivity:	0		
HMIS - Hazard	ous Materials Identification Syste	m	
Health:		3*	
Fire:		1	
Reactivity:	0		

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

# WHMIS Classification(s):

Class D2A - Carcinogenicity Class D2A - Chronic Toxic Effects Class E - Corrosive Material

# WHMIS Hazard Symbols:





Blue = Health Red = Flammability Yellow = Reactivity White = Special

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

#### **CP65 California Proposition 65**

#### OSHA (O) **Occupational Safety and Health Administration.**

ACGIH (G) American Conference of Governmental Industrial Hygienists.

- A1 Confirmed human carcinogen.
- A2 Suspected human carcinogen.
- A3 Animal carcinogen.
- A4 Not classifiable as a human carcinogen.
- A5 Not suspected as a human carcinogen.

Trade Name: Unisorb® Premium Non-Shrink Grout





# INSTALLATION TECHNOLOGIES

Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards

IARC (I)	<ul> <li>International Agency for Research on Cancer.</li> <li>1 - The agent (mixture) is carcinogenic to humans.</li> <li>2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.</li> <li>2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.</li> <li>3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.</li> <li>4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.</li> </ul>
NTP (N)	National Toxicology Program. 1 - Known to be carcinogens. 2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Date of Preparation:	September 12, 2012
Expiry Date:	September 12, 2015
Version:	1.0
Revision Date:	September 12, 2012

**Disclaimer:** We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by:	Nexreg Compliance Inc. Phone: (519) 488-5126 <u>www.nexreg.com</u>
Prepared for:	UNISORB, Inc.

# **End of Safety Data Sheet**